



TECHNICAL DATA

FULLY SYNTHETIC & SEMISYNTHETIC SUPREME DIESEL ENGINE OIL SAE 5W20

PRODUCT DESCRIPTION:

SAE 5W20 DIESEL ENGINE OIL is a high performance, heavy duty multi-grade engine oil, designed to meet the requirements of highly rated four-stroke diesel engines. It is based on high quality mineral base stocks and advanced additives technology providing superior dispersancy / detergency, wear and oxidation resistance properties. A prime recommendation for mixed fleet use having a variety of different makes of heavy duty diesel engines and using fuels of a wide range.

PERFORMANCE LEVEL:

API CH-4/ CJ-4/CI-4

APPLICATION:

- Medium speed diesel engines.
- Marine propulsion and auxiliary engines operating on residual fuel.
- Suitable for stationary equipment such as Pumps, that runs under steady state conditions.

BENEFITS & ADVANTAGES:

- Exceptional detergency and anti-wear properties.
- Effective control of soot, sludge and piston deposits.
- Extended drain capability.
- Excellent high temperature properties.

SPECIFICATION & TECHNICAL PARAMETER:

SAE Grade	Method	5W20
Viscosity @ 100 °C	ASTM D 445	8.5
Viscosity @ 40 °C	ASTM D 445	50.9
Viscosity Index	ASTM D 2270	144
Pour Point, °C	ASTM D 97	-33
Flash Point, °C	ASTM D 92	230
Total Base Number	ASTM D 2896	7.2

*Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.

**All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. It is the user's with all applicable obligations laws and regulations to. For evaluate more information, and use please contact your sales representative.