



TECHNICAL DATA

P-680 AUTOMATIC TRANSMISSION FLUID ATF DEXRON III

PRODUCT DESCRIPTION

ATF DEXRON III is a universal type transmission fluid for use in modern automatic gear boxes where General Motors Dexron III is required. It has a high viscosity index, low pour point and special additives to increase oxidation resistance, rust and corrosion protection and anti-wear properties. It is also highly suitable for power steering units in passenger cars and commercial vehicles.

PERFORMANCE LEVEL

- GM DEXRON III-G
- FORD MERCON
- ALLISON C-4
- CATERPILLAR TO-4

BENEFITS & ADVANTAGES

- Anti-wear properties.
- Compatibility with seal materials.
- Protection against deposit formation.
- Fluidity over a wide range of temperature.

SPECIFICATION & TECHNICAL PARAMETER

#	Test	Method	Result
01	Viscosity Grade	GM	DEXRON III
02	Color	Visual	Red
03	Kin.Viscosity @40 °C	ASTM D 445	34.65
04	Kin.Viscosity @100 °C	ASTM D 445	7.595
05	Viscosity Index	ASTM D 2270	195
06	Density @ 15 °C	ASTM D 1298	0.849
07	Foam Sequence I.II.III	ASTM D 892	0/0
08	Flash Point °C	ASTM D 92	198
09	Pour Point ° C	ASTM D 97	-45

** All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. **