



TECHNICAL DATA

BRAKE FLUID DOT 3

PRODUCT DESCRIPTION

Brake Fluid DOT 3 is a high-quality brake fluid blended from glycol ethers and Polyglycols. It is formulated to contain oxidation and corrosion inhibitors to enhance its chemical stability

- Consistent and safe brake performance under high braking pressure.
- Reduces leakage and loss of fluid to a minimum.
- Improved life and reliability of brake system components.

BENEFITS AND ADVANTAGES

- High boiling point to prevent vapor forming in brake systems.
- Firm braking pressure in all operating conditions.
- Excellent chemical stability.
- Protects metals and rubbers used in brake and hydraulic systems.

SPECIFICATION & TECHNICAL PARAMETER

Test	Method	Result
Appearance	Visual	Bright clear liquid
pH	SAE J1703	7-11
Viscosity at 40°C, cSt	ASTM D-445	1250
Viscosity at 100°C, cSt	ASTM D-445	1.5 min
Boiling Point(ERBP) °C	SAE J1703	Min 240
Flash Point °C	ASTM D-92	121
Pour Point, °C	ASTM D-97	-50
Specific Gravity	ASTM D-1298	1.03

*Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.

**All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. For more information, please contact your sales representative.