

MOLYGULF SPECIALIZED LUBRICANTS

Ultimate High Performance Specialty Lubricants



FG-170 USDA H1 FOOD GRADE SYNTHETIC PNEUMATIC AIRLINE OIL



FG-170 is USDA H 1 authorized very light pneumatic oil specially designed for food Processing air tool, lubricators.

Its meet the ultimate requirement of pneumatic oil, rust and corrosion inhibiting, it fortified with unique food grade additives, yet never decline corrosion inhibiting capability, and protect parts against moisture and acid.

Its contain an emulsifying properties that causes the oil to combine with water to prevent water from wetting metal surface and displacing lubricant. It provide continuous lubrication even under the water contamination.

It Is carefully blended with selective food grade Anti-Wear chemicals additives, which provide excellent extreme pressure properties to protect air operated tools from seizure, help to extend air equipments (like: air gun, cylinder, air pump etc...) life span, and protect the moving part.

It has high viscosity index, resist from oxidized, keep equipments clean, no gumming or deposits left over.

It provide excellent atomization into airlines ahead of air tools, with least dropping along the lines.

TYPICAL SPECIFICATIONS:

MOLYGULF SPECIALIZED LUBRICANTS

Ultimate High Performance Specialty Lubricants



Typical Specification :

ISO VG.....	32
SAE Grade.....	10
Gravity, ° API.....	33.0
Rust Test.....	Pass
Viscosity:	
cSt @ 40 ° C.....	32
cSt @ 100 ° C.....	5.2
Flash Point, ° C (° F).....	182(360)
Fire Point , ° C (° F).....	204(400)
Pour Point, ° C (° F).....	-45.5(-50)
Viscosity Index	115