

TECHNICAL DATA

P-500 SUPREME HYDRAULIC OIL ISO 150

P-500 Is truly Multi-purpose for All Kinds of Hydraulic Systems, Lubricators, Oil Circulating Systems, and General Machinery Lubrication and scientifically formulated from high quality, solvent - refined paraffin base stocks with the most advanced features:

- High VI paraffin base stocks, retain uniform viscosity over wide temperature Range
- Exclusive anti oxidation inhibitor for long life at elevated temperatures
- Good foam dispersant additive
- Superior rust and corrosion protection
- Quick water separation capability
- Improved pliability of seals, reduce oil leakage and consumption

PRODUCT INFORMATION

P-500 is the most advanced multipurpose oil, carefully refined with selected premium base stocks and advanced additive chemistry an exclusive oxidation and wear inhibitors to provide much longer service life.

TYPICAL SPECIFICATION

ISO Viscosity	150				
SAE GRADE	40				
GRAVITY, °API	27.8				
SPECIFIC @ 15.6 ° C	0.892				
VISCOSITY :					
SUS @ 100 ° F	789				
SUS @ 210 ° F	78.0				
cST @ 40 ° C	150				
cST @ 100 ° C	14.6				
VISCOSITY INDEX	95				
POUR POINT, ° F (° C)	10				
FLASH POINT, ° F (° C)	485				
DISTILLED WATER		PASS			
SALT WATER		PASS			
COPPER CORROSSION: 3hrs @ 100 ° C Color	1 Base oil				