



TECHNICAL DATA

P-500 SUPREME HYDRAULIC OIL ISO 32

P-500 Is truly Multi-purpose for All Kinds of Hydraulic Systems, Lubricators, Oil Circulating Systems, and General Machinery Lubrication and scientifically formulated from high quality, solvent - refined paraffin base stocks with the most advanced features:

- High VI paraffin base stocks, retain uniform viscosity over wide temperature Range
- Exclusive anti - oxidation inhibitor for long life at elevated temperatures
- Good foam dispersant additive
- Superior rust and corrosion protection
- Quick water separation capability
- Improved pliability of seals, reduce oil leakage and consumption

PRODUCT INFORMATION

P-500 is the most advanced multipurpose oil, carefully refined with selected premium base stocks and advanced additive chemistry an exclusive oxidation and wear inhibitors to provide much longer service life.

TYPICAL SPECIFICATION

ISO Viscosity	32
SAE GRADE	10
GRAVITY, °API	29.9
SPECIFIC @ 15.6 ° C	0.877
VISCOSITY :	
SUS @ 100 ° F	166
SUS @ 210 ° F	44.2
cST @ 40 ° C	32.2
cST @ 100 ° C	5.3
VISCOSITY INDEX	99
POUR POINT, ° F (° C)	0(-17.7)
FLASH POINT, ° F (° C)	403(206)

DISTILLED WATER.....PASS.....

SALT WATER.....PASS.....

COPPER CORROSION:

3hrs @ 100 ° C	1	1	1	1	1
Color	Base oil	Base oil	Base oil	Base oil	Base oil