

MOLYGULF SPECIALIZED LUBRICANTS

Ultimate High Performance Specialty Lubricants



MG-270 SPECIAL EXTREME PRESSURE GREASE



MG-270 is a Premium Extreme Pressure, Multi-Purpose Grease, specially formulated for all type Industrial & Automotive application. It is Truly Multi-Purpose, One Grease for all type of Automatic Pumpable, Centralized Bearings, Including Plain Bearings, Heavily Loaded Journal Bearings, Ball and Roller Bearings, Needle Bearings, Chassis and Excellent for most Automotive, Construction, Mining, Farming and Industrial Equipments.

FEATURES:

1. Truly multi-purpose for all types of bearings.
2. Excellent pump ability characteristics with grease gun.
3. Excellent shear and mechanical stability.
4. Excellent Extreme Pressure properties.
5. Excellent water wash out resistant.
6. Excellent adhesives and cohesive properties

MOLYGULF SPECIALIZED LUBRICANTS

Ultimate High Performance Specialty Lubricants




TYPICAL SPECIFICATIONS:

NLGI		1	2
Appearance		Golden	Golden
Cone penetration		260	245
Dropping point C		215	230
Corrosion to Copper Strip (25 C X 24HR)		Negative	Negative
Oil separation		4.10	4.10
Work stability		245	260
Oxidation stability PSI		7.00	7.00
Difference 60 and 10,000 60 and 100,000		11+ 16+	11+ 16+
Texture		Smooth	Smooth
Water by distillation , %		0.05	0.05
Soap content , %		8.50	8.50
Base Oil viscosity		775	775

MOLY GULF SPECIALIZED LUBRICANTS

Ultimate High Performance Specialty Lubricants



NLGI	0	00	000
Appearance	Yellowish	Yellowish	Yellowish
Cone penetration	268	280	325
Dropping point C	210	205	200
Corrosion to Copper Strip (25 C X 24HR)	Negative	Negative	Negative
Oil separation	4.10	4.00	3.95
Work stability	210	210	210
Oxidation stability PSI	7.00	7.00	6.80
Difference 60 and 10,000	11+	10+	10+
60 and 100,000	16+	15+	15+
Texture	Smooth	Smooth	Smooth
Water by distillation , %	0.05	0.05	0.05
Soap content , %	8.50	8.50	8.50
Base Oil Data			
viscosity			
cST@40 C	228	228	228
cST@100 C	13.5	13.5	13.5
Timken Load	45	45	45