



# TECHNICAL DATA

## P-660 SPECIAL PNEUMATIC OIL ISO 15

**P-660** Is truly Multi-purpose, Pneumatic ‘Air Line’ Lubricators, Oil Circulating Systems General Machinery Lubrication and scientifically formulated from high quality, solvent - refined paraffin base stocks with the most advanced features:

**PRODUCT INFORMATION P-660** is the most advanced multipurpose oil, carefully refined with selected premium base stocks and advanced additive chemistry an exclusive oxidation and wear inhibitors to provide much longer service life. It is specifically formulated for air-line system, it meet and exceed all specification

- Good emulsifier
- Excellent foam resistant and air separation
- Excellent extreme pressure properties to part seizure
- Good adherence to wet surface
- Good rust preventive properties
- Provide proper atomization into air lines ahead of tool.

### TYPICAL SPECIFICATION:

<b>ISO Viscosity</b>	<b>15</b>
SAE GRADE	
GRAVITY, °API	
SPECIFIC @ 15.6 ° C	0.877
VISCOSITY :	
SUS @ 100 ° F	166
SUS @ 210 ° F	44.2
cST @ 40 ° C	32.2
cST @ 100 ° C	5.3
VISCOSITY INDEX	99
POUR POINT, ° F (° C )	0(-17.7)
FLASH POINT, ° F (° C )	403(206)

DISTILLED WATER.....PASS.....

SALT WATER .....PASS.....

### COPPER CORROSION:

3hrs @ 100 ° C	1	1	1
COLOR	Colourless	Colourless	Colourless

\*\* All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. It is the user’s obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. \*\*



# TECHNICAL DATA

---