



TECHNICAL DATA

RADIATOR COOLANT 50%

PRODUCT DESCRIPTION

Radiator Coolant 50% is recommended for use in liquid cooling systems of automotive and industrial gasoline and diesel engines. They are available in various concentrations ready for use. The higher boiling points of radiator coolant are beneficial in hot weather and at high altitudes.

APPLICATIONS

- Protects cooling systems of gasoline and diesel engines against rust in all seasons.
- They provide ideal cooling, effective protection against corrosion and scale deposit formation in the cooling systems.
- Longer radiator life and lower maintenance cost.

BENEFITS & ADVANTAGES

SFSF

- High boiling point gives better cooling performance in high temperature condition.
- Excellent anti-foam properties.
- Withstands freezing at low temperatures.
- Protects the radiator against rust & corrosion.
- Compatible with ordinary summer coolant.
- Protection against excessive evaporation.
- Provides year round cooling and anti-freeze properties.

S#	Test	Method	Result
1.	Concentration	-	50%
2.	Colour	Visual	Flu.Green
3.	Appearance	Visual	B&C
4.	Density @20 ° C	ASTM D 1298	1.07
5.	pH	ASTM D 1297	7.9
6.	Reserve Alkalinity	ASTM D 1121	3.5
7.	Freezing Protection	ASTM D 1177	-36
8.	Mono Ethylene Glycol Concentration	Distillation	49.8
9.	Chloride	D 3634	< 20

** All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. **