



TECHNICAL DATA

FULLY SYNTHETIC & SEMI SYNTHETIC SUPREME PETROL ENGINE OIL SAE 30

SAE 30 – is a new revolution Multi Grade Engine Oil that meet today’s most stringent requirement of high performance engine and fuel efficient, low emission engine. This product was specially designed for use in sports cars and luxury vehicles. **SAE 30** is formulated with finest quality base oil, are designed to meet all major engine:

FEATURES:

- Longer Interval between Oil changes.
- Longer Service between Engine Overhaul.
- Excellent Corrosion Protection.
- Dramatic Fuel Saving.
- Keeps Engines Clean.
- API Engine Service Classified.
- Minimized Piston Rings and Cylinder Liner Wear.

One Oil for All Engine Services. **SAE 30** can be used for all types of Engine purpose, **SAE 30** is also superior for Automotive Engine Set in all services reduces inventory and misapplication is avoided.

- Excellent Wear and Deposit Protection of Off-Highway Petrol Engines.
- Exceptional Thermal Stability, for Outstanding Performance at High Engine Operating Temperatures.
- Viscosity index improver which will not make the oil thinning during high temperature and thicken during low temperature.

Excellent Anti-Foaming Properties to Protect Against Aeration and Foaming.

TYPICAL SPECIFICATIONS:

SAE Grade	Method	30
Viscosity@100°C, cSt	ASTM D 445	10.6
Viscosity@40°C, cSt	ASTM D 445	102
Viscosity Index	ASTM D 2270	102
Pour Point	ASTM D 97	-36
Flash Point, PMCC, C min	ASTM D 92	230
Density @15°C, Relative	ASTM D 1298	0.893