



TECHNICAL DATA

P-510 SUPREME COMPRESSOR OIL SERIES 150

PRODUCT DESCRIPTION

Supreme Compressor Oils are blended from premium paraffinic base oils of high viscosity index and modern additive technology that give these fluids a unique control over oxidation, rust, corrosion and wear. The ash less additive system enables the use of these oils in both reciprocating as well as rotary compressors. Supreme Compressor series strictly conform to the ISO viscosity grading system.

APPLICATION

- Suitable for oil-flooded rotary compressors
- Provides excellent lubrication in sliding vane compressors and in reciprocating compressors operating at high ambient temperatures
- Can also be used in crankcase and cylinders of reciprocating compressors.

Benefits and Advantages

- Reduced compressor deposits
- Reduced wear – protects against friction, corrosion and rust
- Superior oxidation stability
- Reduces crankcase oil consumption

SPECIFICATION & TECHNICAL PARAMETER

AIR COMPRESSOR

ISO GRADE	150
SAE GRADE	40
Color	2.0
Kin.Viscosity @ 100 ° C	15.02
Kin.Viscosity @ 40 ° C	156.2
Density @ 60/60F	0.89
Viscosity Index	97
Pour Point	-13
Flash Point	250
WATER CONTENT	-ive
Foam Seq I, II, III	PASS

* Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.

** All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations.